



**Flashing:** The 'Corrugator™' requires no additional flashings nor sealing other than the application of the enclosed EPDM self adhering sealing/separation strip. If there is any doubt as to the weatherproofing of the ladder bracket within the pan, an appropriate silicone application may be considered by the installer.

## 6. AVAILABILITY AND COST:

Contact **Secure Anchor Systems** for current pricing and supply information for Australia and New Zealand.

## 7. MAINTENANCE:

The Trimdek® TD06™ Ladder Bracket should be checked annually at the very least by a 'competent' person as required and/or detailed in Government OH&S Acts, Codes of Practice and all applicable building codes. Ensure that the Trimdek® TD06™ is firmly attached to the roof and not loose with the use of all screw fixings as detailed in 4. Technical Data above. Ensure all safety equipment to be used in conjunction with the Trimdek® TD06™ Ladder Bracket is checked prior to use.

If there is any doubt or non surety as to the performance of any installed Trimdek® TD06™ Ladder Bracket DO NOT USE OR ATTACH TO IT and contact a certified practising structural engineer or Secure Anchor Safety for further direction.

## 8. TECHNICAL SERVICES:

Technical support and assistance is available through **Secure Anchor Systems**.



For additional information and literature contact **Secure Anchor Systems: Telephone 1300-131-881 | Facsimile 1300-731-881**

**NATIONAL OFFICE:**  
Unit 26, 56-58 O'Riordan Street  
ALEXANDRIA NSW 2015

TELEPHONE: 1300 131 881  
FACSIMILE: 1300 731 881

EMAIL: [info@secureanchor.com.au](mailto:info@secureanchor.com.au)

© Copyright American Shingles Pty Limited, 1 January, 2014. All rights reserved.